



ENGINE

Type Single cylinder, 4 stroke, Air-Oil cooled

Displacement 349cc

Bore x stroke 72 mm x 85.8 mm

Compression Ratio 9.5:1

Maximum Power 20.2 BHP @ 6100 rpm Maximum Torque 27 Nm @ 4000 rpm

Ignition System Electronic Fuel Injection(EFI)

Clutch Wet, multi-plate

Gearbox 5 Speed constant mesh

Lubrication Wet sump, forced lubrication

Engine Oil SAE 15 W 50 API, SL grade, JASO MA 2 Semi Synthetic

Fuel Supply Electronic Fuel Injection

Air Cleaner Paper element

Engine Start Electric

CHASSIS & SUSPENSION

Type Twin Downtube Spine Frame

Front suspension Telescopic, 41mm forks, 130mm travel

Rear suspension Twin tube Emulsion shock absorbers with 6-step

adjustable preload

DIMENSIONS

Wheelbase 1400 mm
Ground Clearance 170 mm
Length 2140 mm

Width 845 mm (without mirrors)

Height 1140 mm (without mirrors)/ 1310 mm (with windscreen)

Seat Height 765 mm

Kerb Weight 191 kg (with 90% fuel & oil)

Fuel Capacity 15 ltr

BRAKES & TYRES

Tyres Fr. Alloy Wheel - 100/90 - 19" - 57P (Tubeless Type)
Tyres Rr. Alloy Wheel - 140/70 - 17" - 66P (Tubeless Type)
Brakes Front 300 mm disc with twin piston floating caliper
Brakes Rear 270 mm disc, single piston floating caliper

ABS Dual Channel

ELECTRICALS

Electrical System 12 volt - DC

Battery 12 volt, 8 Ah, VRLA (maintenance free)

Head Lamp 12V, H4-60/55W (Halogen) with LED light guide

Tail Lamp 12V, LED type - 2.4/1.2W

Turn Signal Lamp 12V, 10W X 2 nos

COLORS

Fireball Yellow, Fireball Red, Stellar Black, Stellar Red, Stellar Blue, Supernova Brown Supernova Blue.